

P=10.0mm, N为孔位数 (N for hole digits), 有效位数为 (Significant Digits): 02P~12P


N	02P	03P	04P	05P	06P	07P	08P	09P	10P	11P	12P
L	16.60	26.60	36.60	46.60	56.60	66.60	76.60	86.60	96.60	106.60	116.60
B	10.00	20.00	30.00	40.00	50.00	60.00	70.00	80.00	90.00	100.00	110.00

版次 (Version)	变更内容 (Rev. Content)	变更者 (Change Person)

技术参数 (Technical Data)		
项目 (Item)	UL	IEC
额定电气参数 (Rated Electrical Parameters)	600V/20A	1000V/24A
压线范围 (Wire Range)	18~12AWG	0.5~2.5mm ²
工频耐压 (Frequency Voltage)	AC 3000V	
冲击耐压 (Rated Surge Voltage)	6000V	
绝缘阻抗 (Insulation Resistance)	DC500V 500MΩ above	
接触电阻 (Contact Resistance)	≤8mΩ	
剥线长度 (Stripping Length)	6~7	
工作温度 (Temperature)	-40℃~+105℃	
材质和电镀 (Material and plating)		
绝缘材质 (Housing)	PA66 (UL94 V-2)	
接线柱 (Contact Block)	铜合金, 镀镍 (Copper alloy, Ni plated)	
螺丝 (Screws)	钢, 镀锌 (Steel, Zn plated)	

产品命名编码:
(Product Number Code):

GSS200HW-10.0-XXP-1Y-00A (H)



- | | |
|------------------------|-----------------------|
| 1: 单倍间距 (Single Pitch) | 7: 透明色 (Transparent) |
| 2: 双倍间距 (Double Pitch) | 8: 白色 (White) |
| | 9: 黄色 (Yellow) |
| | Y: 多种颜色 (Mixed Color) |
| | 6: 红色 (Red) |

宁波高胜电子有限公司 NINGBO GOOSVN ELECTRONIC CO.,LTD		公差范围 (Tolerance Range)	
		150~	±1.50
型号 (Type): GSS200HW-10.0-XXP-1Y-00A (H)		30~60	±0.60
核准 (Approval):		6~30	±0.40
审核 (Audit):		0~6	±0.25
设计 (Design):		角度 (Angle)	X ±2° XX ±1°
比例 (Scale): FULL		版次 (Version): T0	